

**TECHNICAL FEATURES**

<b>Trade Name</b>	Weighing bottles
<b>Use</b>	Reduce the tare weight correction during precision weighing
<b>Material</b>	Polypropylene PP
<b>Other features</b>	Airtight push on lids included

**DIMENSIONAL FEATURES**

<b>Capacity</b>	360 ml
<b>External diameter</b>	70 mm
<b>Height</b>	118 mm
<b>Tare</b>	40 g

**GENERAL FEATURES**

<b>CE mark</b>	No
<b>Foodstuff suitability</b>	Yes
<b>Translucency</b>	Yes
<b>Resistace to acid attack</b>	Hight
<b>Shoulders</b>	No internal shoulders to allow use of spatula
<b>Top</b>	Squeazable top to assist pouring

**Assicurazione Qualità**

**STERILIZATION**

Autoclavability atT +121°C	Yes without lid (remove lid before autoclaving)
Gas (Ethylene Oxide)	Yes
Dry at 160°C	No
Chemical (Formalin)	Yes
Radiations	Yes
Microwave	Yes

**CHEMICAL RESISTANCES**

Categories of substances	Reference	Concentration %	T. 20° C	T. 40° C	T. 60° C
Inorganic Acid	Sulphuric acid	98	B	C	
Organic Acid	Benzoic acid	100	A	B	B
Alcohol	Ethanol	100	A	A	A
Aldehydes	Acetaldehyde	100	B	C	-
Inorganic alkali	Sodium hydroxide	50	A	A	A
Organic alkali	Aniline	100	A	B	C
Ketone	Acetone	100	-	-	-
Esther	Ethyl acetate	100	B	B	C
Hydrocarbons, halogenated	Dichloroethylene	100	C	-	-
Hydrocarbons, aromatic	Benzene	100	B	C	-
Hydrocarbons, linear	Hexane	100	B	B	C
Supersolvent	Tetrahydrofuran	100	B	B	C

**Legenda** (not applicable if neglected):

- **A: fair resistance;** exposure (30 days) to the chemical does not cause any damage.
- **B: sufficient resistance;** exposure causes damage of poor importance, which sometimes is only temporary.
- **C: poor resistance;** exposure to chemical is not allowed, or causes immediate permanent damages.

**Results of testing with reference materials are to be considered as indication: in case of specific use it is recommended to carry out preliminary testing.**

Information about resistance of plastic materials to temperatures, steriization and washing treatments are based on bulletins issued by the Producers of raw materials , on literature data and on the experience gained in using the products

**PACKAGING**

Box	10 pcs
-----	--------

**Assicurazione Qualità**