

Product: Dri-Fresh® Safe-Hold™ 3000 Xtra Inflex pouch (4-bay)

Item Code: 814H0000024

Structure: Dri-Fresh® Safe-Hold™ 3000 Xtra Inflex consists of a thermally bonded two-layer structure as follows:

Top layer: Thermally bonded, direct food contact approved, PE coated Inflex paper

Absorbent layer: Proprietary blend of absorbent and bonding fibres, including superabsorbent fibres

Absorbency: Nominal absorbency – 3000 cc/m²

Absorbency per pouch – 36cm³

Minimum absorbency tolerance is 25% below the nominal

Absorbency based on Sirane absorbency test procedure (details on request)

*Due to processing of material and lamination properties the absorbency of the products will on occasion be below the nominal figure. Testing should be conducted to ensure that the pad and required absorbency is suitable for the required application.

Pouch construction: The pouch will be formed using thermal lamination technology. The raw materials will be slit then creased with thermal seals input at either side and centrally to form the Dri-Fresh® Safe-Hold™ pouch and form 4 separate bays.

Dimensions: Depth: 125mm x Width: 226mm +/-10mm

Pouch has 10mm seals on each edge +/-3mm

Pouch inner width is 50mm +/-3%

Pouch depth is 120mm +/-3%

The lip on the pouch will be 5mm +1mm/-3mm

Weight: 6.26 grams

Packaging: Boxed in blue, food-grade liners. Box size: 318 x 318 x 432mm. Quantity: 500pcs

Palletising: Boxes shrink-wrapped on pallet. Cases / pallet: 24.

Labeling: Individual box label includes product description, dimensions, colour, traceability code, customer specified product code, order number, box quantity and box number. Plain labels to be used. 2 labels per box on adjacent sides.

Pallet label includes customer name, delivery address, product description, dimensions, colour, traceability code, customer specified product code, box quantity, pallet quantity and shipping date.

