

Product Name: **Micrewtube®**

Catalogue No.: **T339-5S**

This document replaces any previous version

1. Product Description:

- **1.5ml Micrewtube®:** Sterile, conical bottom with lip seal and flat screw cap. Caps are screwed on and tubes are non-graduated.

2. Packaging:

- **Case:** 10 packages of 50 units / 500 units per case

3. Product Specifications:

- **Material:**
 - Polypropylene tube;
 - Polyethylene cap.
- Certified RNase, DNase, Pyrogen and DNA-free;
- Gamma radiation sterilized at a SAL of 10^{-3} ; specified dose between 6.5 kGy and 12.5 kGy;
- Temperature range: -196°C to +100°C.;
- Tubes have no graduations and have no writing areas;
- Caps have flat top writing surface;
- Centrifuged up to 20 000 g.

4. Standards and Conformity:

- **ISO 2859-1:** Sampling and inspection procedures
- **FDA:** Resin conforms to FDA 21 CFR 177.1520
- **USP:** Resin conforms to USP Class VI
- **CONEG:** Plastics and colorants are in conformity with CONEG standards for heavy metals
- **REACH (SVHC):** Plastic is in conformity to REACH standards
- **LATEX:** Material is Latex free
- **BSE / TSE:** Material is BSE / TSE free

5. Quality Assurance:

- Clear, no presence of contamination in plastic;
- Visual attributes;
- Volume measurements;
- Closure verification;
- Leak proof testing in vacuum at 71.3cm Hg;
- Gas phase of Liquid Nitrogen resistance.

6. Traceability:

- **Lot No. Composition:** 8 to 9 digits

- **The lot number can be found in one or all of these locations:**
 1. On exterior case label;
 2. On label inserted inside the master case;
 3. On the inner bag.

7. Storage Conditions:

- Store at room temperature in normal warehouse conditions;
- Avoid temperature variations and humidity;
- Protect from any possible contamination;
- Protect from any damage to the packaging which could compromise the product sterility.

8. Recommended Use:

- Verify proper cap closure when using biohazard material and / or chemical reagents;
- Follow chemical resistance chart recommendations;
- For use in automated equipment, follow the equipment manufacturer's instructions;
- Should be used only in the gas phase of Liquid Nitrogen.

OWNERSHIP OF MATERIALS:

*Materials and information contained in this document are **Simport Scientific's** copyrighted and are protected by worldwide copyright laws and treaty provisions. They may not be copied, reproduced, modified, published, uploaded, posted, transmitted or distributed in any way.*